

		
		V1.5
		
	IR-808-1500-S-05	
	K10010142	
	L*W*H=171*66*76mm	
J J J J J J J J J J J J J J J J J J J J		
J J J J J J J J J J J J J J J J J J J J		
	LGL	2022 07 23
	LZHJ	2022 07 23
	WYM	2022 07 23



	IR-808-1500-S-05
	•1500
	808±5nm
	Class 4 FDA Ⅱ IEC
	60m
	0.8° 70°
	Ⅲ 3 -
	10W
	•8W
	0.8° Ⅲ 1500 21
	70° Ⅲ 40 56
	DC12V±10%
	2.5A±0.3A
	Ⅲ 35W
	RS-485 Ⅱ TTL Ⅱ (: 9600bps)
	Pelco_D
	-35 +55
	-40 ~+70



. P *™ H

;ç0 Šgx

- 1 Ã \ × ñ Ž ¾ 4 2«MŽ ?ñ y%ð y ~ È X%ð y&Ÿ 0 _,(æ 1 ; È U/±+X-IF6 y-\$?ö F65 ¯+X y –
~F6 y?ò %ð y y • Ä
- 2 Ã X!“ h ¯+X,´ ð å ; ÈKÆ d } é 100cmµ U/± 9 C'ó(™ fFž Q È Lb +O&>&@ Ä
- 3 Ã \ × ñ X ¯+XE÷0; J È× ñ Ä>ð X ê-l # -\$?ö,´ }5ž ÈF65/è ê-l-\$?ö,´ }5ž 9Că O,´D /è
² æ Ä i ž- x,´ j Ÿ È&¥#kF9 %ð y ~,´EÄ 4 İ). È Lb × ñ) ê-lFP @,´ • ã Ä
- 4 Ã ² æ X ¯+X A (,´ × ñ & È Ä X × ñ,´ FG Cd 9%ð yEÄ 4A– z 71® Ä
- 5 J ² æ X ¯+XE÷0; J²)à ~ & uLì ÈB' 6 × ñ ô A œ (F >|5\$ È = /ñ8 ö ¨ È/ñ8 ö ¨
> = ½F >|CX Ä

OSKú à/n

œ (=0 Ö\$! c 2 9 s2£ y+e0 ° 9L€ œ (
J Ñ+eB Ö07556686 4401
œ (5•1 Ö www.sz3km.com
+e €Fp1á Œales@sz3km.com
œ (` p Ö\$! c 2 Í¹ j"É Ä>‡Ff : ‡ LD 128 ', <9"Q à × J 1 ; 12 ¬