

	Mi(>¿ H@f5 9 MÃ	
--	------------------	--

“#Â&Œ"ø

IR-

JD6"Ã4q	
gzEï	"Ã4q
``#Â# Hñ	gl = 5oMj(>¿ HWd H?n
``#Â&Œ"ø	IR-940-1500-S
6 4l\pH¼	1500 Kr
>Á J%iKj&Œ	HME!ÿ" >¿ H%g
"Ò J;ãd€	940±10nm
>Á J*Š iJjM``	Class 4 o FDA ;IEC o
>Á J*Š il\pH¼	5ÿ+ XÑ-¥4ð60m
@h5 XÓ-§	D4!§# :d"×@%o 0.8oe70°^ÝMì"ĩ[
"Ù 4÷dð	M3 HÑo ^ÛXÑÐXÑo
>Á JQ°AH! B^	12W
û J! B^	10W
@h5 XÓ-§	^ÛXÑ0.8°o!6 4G\ÜH° N1500 Kro H4•Eó.f 21 Kr
	^ÐXÑ70°o!6 4G\ÜH° N40 Kro H4•Eó.f 56 Kr
@h5 4l6•	gl = 5oWd H1•6.o H4•^,DK= 5oo --¥&F!ÿo *¿ g4ß4b4•o D:\'MÅ Pz__ o _ ?þeçeyf=4G6>Qn(
,æ]D6"Œ	DC12V±10%
,æ]D6<B	1.9A±0.3A
4u6;! O	M28W
_ â4°.	RS485 ; 1"â TTL;1J!§2;!5"ĩ_ (m×Z£9600bps)
_ â"PZ`	Pelco_D

7 Ç,æ]=*-§	-35qàoe+55qà
©*Y=*-§	-40qà~+85qà
4u6;+ #~	o%2000Θ
(XÃ+;*ù	171*66*76mmo L*W*Ho
ˆÎĐ	<550g
B° ЪZ¥ZÂ	4s69RoHSZ£ZÀ

1 ч

4

III

2 ч

100cm

III

3 ч

III

,

4 ч